



Motorola RAZR Maxx HD Front-Facing Camera Replacement

Use this guide to remove the front-facing camera.

Written By: Jacob Syage



INTRODUCTION

The front-facing camera is an independent part attached to the main LCD display frame. This guide involves the removal of various screws and parts so make sure you are in a clean and organized environment to avoid the loss of any components.



TOOLS:

- [Spudger](#) (1)
 - [Tweezers](#) (1)
 - [T3 Torx Screwdriver](#) (1)
 - [Paper Clip](#) (1)
 - [T5 Torx Screwdriver](#) (1)
-

Step 1 — Screen Removal




- Use the Torx T5 Screwdriver to remove two 5.0 mm screws at the bottom of the phone.

Step 2




- To remove the SIM card, use an unfolded paperclip to press down on the metal plate on the left side of the phone until it pops up.


Step 3



- Gently push the screen toward the top edge of the phone and tilt the screen to reveal the black flex cables.

 Do NOT remove the screen all the way or the flex cables will be damaged.

Step 4



- Release the two black ribbon flex cables by gently pulling up on the connection using the spudger. Then lift the screen to remove.

⚠ Make sure to remove the flex cables before completely removing the screen.


ⓘ When reassembling, align the white bands on the edge of the screen so that a connection is made.

Step 5 — Front-Facing Camera




- On the back of the LCD display, release the yellow front-facing camera ribbon cable by gently lifting upward on the black retaining clip with the spudger.

Step 6



- With a Torx T3 screwdriver, unscrew the two 2.0 mm screws on front-facing camera mounting bracket. Then lift to remove it.

Step 7



- Use tweezers to remove the front-facing camera by lifting it from the LCD display frame.

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2017-06-26 05:20:34 AM.